



**ROTARY AXIS (回転軸)**

INDEXING ACCURACY 20 sec  
 CLAMPING TORQUE 1568N・m  
 SERVO MOTOR FANUC  $\alpha$ IFB/3000  
 TOTAL REDUCTION RATIO 1/90  
 RAPID SPEED 22.2m/min  
 TILT AXIS (傾斜軸)  
 INDEXING ACCURACY 60 sec  
 CLAMPING TORQUE 1568N・m  
 SERVO MOTOR FANUC  $\alpha$ IF12/3000  
 TOTAL REDUCTION RATIO 1/90  
 RAPID SPEED 22.2rpm  
 NET WEIGHT 227kg

BLEE LIGHT IN POSITIONAL POSITION (0°)  
 WIDTH OF T-SLOT 11.1mm  
 WIDTH OF GUIDE BLOCK 11.1mm  
 TILT AXIS TRAVEL 11.1mm  
 MAX LOAD 227kg  
 CLAMPING METHOD HYDRAULIC

RU: ROTARY AXIS UNCLAMP R $\phi$ 3/8  
 TU: TILT AXIS UNCLAMP R $\phi$ 8  
 TC: TILT AXIS CLAMP R $\phi$ 3/8

M16x40L  
 T-SLOT NUT  
 1816-TN  
 FITTING METAL ASSETS (標準品 各1セット)

ROTARY AXIS  
 TILT AXIS  
 1/90  
 1/90

MACHINE MAKER	TITLE	2 PORT TYPE	CUSTOMER
MACHINE MODEL	Tilting Rotary Table		KS-AX350R-FA33T/1
CODE NO.	5AX-350FA		DESIGNED
SCALE	1/5	NIKKEN KOSAKUSHO WORKS, LTD.	CHECKED
DATE	2007/OCT/25	DIR-NAME	APPROVED
		5AX	YOSHIMOTO
		DRWG. NO.	TCA-C1099/0

NIKKEN KOSAKUSHO WORKS, LTD. ALL Rights Reserved